

(19)



JAPANESE PATENT OFFICE

AURIGIN® SUMMARY PAGE

(11) Publication number: **03038592 B2**

(45) Publication Date: **08 . 05 . 00**

Application Publication No.: 03066359 A2

(43) Date of publication of application: 22 . 03 . 91

(51) Int. Cl 7A61B 5/055 7G01R 33/48

(21) Application number: 02184412

(22) Date of filing: 13 . 07 . 90

(30) Priority: 13 . 07 . 89 US 379075

(71) Applicant: **PICKER INTERNATL INC**

(72) Inventor: **SIUCIAK ALAN M
CHATTERJEE CHANDRALEKHA
PALMER NEIL D**

(54) **METHOD AND DEVICE FOR NUCLEAR
MAGNETIC RESONANCE IMAGE**

interfering the next sequence or the other sequence of
the residual magnetization.

(57) Abstract:

COPYRIGHT: (C)1991,JPO

PURPOSE: To eliminate the influence of a residual magnetization by further impressing a resonance diphasing gradient pulse magnetized in a residue in a series of cyclically repeating processes.

CONSTITUTION: In a third crossing direction, it adds a diphasing readout gradient pulse 60 before a data collection. When the data is collected, it adds a primary read-out gradient pulse 62 having a reversible magnetism. A gradient echo 64 is generated at a predetermined position between the primary read-out gradient pulse 62 by performing and sizing in order the timing of the read-out gradient pulse. The diphasing read-out pulse 66 of the residual magnetization is added after the primary read-out gradient. A size of the diphasing pulse of the residual magnetization is a size of not refocussing when the data is collected by the residual magnetization. An area of the diphasing read-out gradient pulse 66 is selected as to a prior read-out gradient pulse and the primary read-out gradient pulse so as to not form an echo at the time of

